

#### Performance

Magnetic performance	4,000 Gauss
	Patented Micromag style core
Volume	0.13 gal (500 ml)
Pressure	43 psi (3 Bar) operating pressure
Flow rate	14 gpm (3 m³/h)
Collection Capacity	0.9 lbs (400 g)
Temperature	212°F (100°C)

Construction<br/>Magnet materialRare Earth Neodymium Iron BoronMesh filter0.5mm, quick release mesh (for cleaning)Valves1" NPT (1.25" NPT adaptors included in kit) OR 1" Press connectionsIncludesAdditional Automatic Air Vent that has been packaged along<br/>with unit separately. The auto-vent will automatically release<br/>trapped air maintaining heating efficiency.WarrantyIndustry leading 3 years

It's all in the box....

All you need to fit and service BoilerMag is contained in a simple retail friendly off-the-shelf package.

BoilerMag filter unit

Automatic Air Vent

- 2 x 1" NPT connections ( 2 x 1½ NPT adaptors) OR 2 x 1" Press connections
  - Product guideDrain valve wrench
    - Boiler sticker

Bowl wrench/cleaning tool

• Spare o-rings



Try our range of high intensity filtration systems for large commercial and industrial installations as well as our system treatment chemicals:



(filter to suit 11/2" pipe)



BoilerMag XT (filter to suit 1½"-12" pipes)



BoilerMag North America 442 Millen Road Unit #9, Stoney Creek, Ontario, L8E 6H2 T 1-800-260-2124 F 1-800-260-1410 sales@eclipsetoolsinc.com www.boilermaq.com/na



A world leader in magnetic technology



v6 f 🕑 🞯 in 🖸





#### **Complete Hydronic System Protection**

### **Full Flow Filter**

- Removes sludge and scale
- Dual flow technology <sup>™</sup>
- Premier performance
- Patented magnetic circuit
- Built to NSF-61 Standards (Domestic water applications)











\*Available in NPT or Press

Connections







## Getting to Know Your BoilerMag

features for installers, service contractors, and property owners.

BoilerMag is designed for performance and practicality. The illustration below highlights the key

# High Performance Air, Dirt, and Magnetite Separator

Combining high performance with ease of installation and servicing, BoilerMag uses tried and tested patented magnetic technology to remove virtually 100% of magnetite (sludge) and scale on the first Simple flush access point pass through the filter. flush attachment available separately Featuring "Dual Flow" technology it is the perfect choice for residential installations. Air vent/chemical dosing point 360° Adjustment -1" NPT (1.25" NPT adaptors included) OR 1" Press connections allows installation at any angle either Install/Clean in minutes, protect for years pipework or filter Any direction install (pipework or filter) Requires minimal access space - unit does not have to be High performance dirt removal fully removed from pipework **Includes Automatic Air Vent** High quality isolation valves included Easy "in-line" installation Easy "In-Line" 6 installation No block feature No block mesh quard removes scale and other non-magnetic debris 8 Patented magnetic circuit - ensures Magnetic core Contamination system cannot block attracted to the cor Fluid channels remain open Patented 9 \*Best value option magnetic core -Why go through the trouble of large magnetic surface area purchasing separate boiler filter 10 Dual flow technology components when BoilerMag, maximizes dirt collection performance The Ultimate Filtration Solution, by ensuring that magnetite is exposed offers all necessary components to the magnetic zone for longer in one package?



